

Technologies specifications

技术参数

牵引车Tractor J6P-6X4

Vehicle type 车辆类型		CA4250	CA4250	CA4250	CA4250	CA4250	CA4250
Drive mode 驱动形式		6×4	6×4	6×4	6×4	6×4	6×4
Cab 驾驶室		J6P high-top extended cab J6P高顶驾驶室	J6P high-top extended cab J6P高顶驾驶室	J6P high-top extended cab J6P高顶驾驶室	New J6P high-top semi- extended cab 新J6P半高顶驾驶室	New J6P high-top extended cab 新J6P高顶驾驶室	New J6P high-top extended cab 新J6P高顶驾驶室
	Model 型号	CA6DL2-35E3F	CA6DM2-42	CA6DM2-42	CA6DL3-37E5	CA6DM2-42E51	CA6DM2-46E52
	Displacement (L)	8.6	11.04	11.04	8.6	11.05	11.05
	Maximum power(hp) 最大马力	350	420	420	375	420	460
Engine 发动机	Rated speed (rpm) 额定转速	2,100	1,900	1,900	2,100	1,900	1,900
	Maximum torque/speed (Nm/rpm) 最大马力转速	1500	1900	1900	1550	1900	2100
	Emission 排放标准	Euro II 欧二	Euro II 欧二	EURO II 欧二	EURO V 欧四	EURO V 欧四	EURO V 欧四
Transmission 变速箱	Model 型号	CA10TA160M2	12JSD200TA	12JSD220TA-B	12JSD180TA	CA12TA210M	CA12TA210M
	Form/number of gears 前进档位数	manual/10 手动/10档	Synchronizer manual/12 同步器手动/12档	Synchronizer manual/12 同步器手动/12档	Synchronizer manual/12 同步器手动/12档	manual/12 手动/12档	manual/12 手动/12档
	Forward gear ratio range 前进挡速比	14.7-1.0	12.1-0.78	12.1-0.78	12.1-0.78	15.6-1.0	15.6-1.0
Front axle load (kg) 前桥载荷 (kg)		7500	7500	7500	7500	7500	7500
Front suspension 前桥悬挂		钢板弹簧	钢板弹簧	钢板弹簧	钢板弹簧	钢板弹簧	钢板弹簧
Rear axle load (kg) 后桥载荷 (kg)		2×13000	2×13000	2×16000	2×13000	2×13000	2×13000
Rear suspension 后桥悬挂		钢板弹簧	钢板弹簧	钢板弹簧	钢板弹簧	钢板弹簧	钢板弹簧
Rear axle model/speed ratio 后桥型号/速比		φ457/4.11	φ457/4.875	φ300/5.921	φ435/4.1	φ457/4.44	φ457/4.11
Chassis self weight (kg) 底盘自重 (kg)		About 8500	About 8850	About 9200	About 8300	About 9000	About 8850
Towing Weight (kg) 牵引重量 (kg)		40,000	50,000	150,000	40,000	50,000	45,000
Wheel base (mm) (轴距)		3450+1350	3200+1350	3450+1350	3450+1350	3450+1350	3450+1350
Saddle 鞍座		φ50	φ90	φ90	φ50	φ90	φ90
Tire 轮胎		12R22.5	12.00R20	12.00R20	12R22.5	12R22.5	12R22.5
Brake system 制动系统		Front and rear independent dual-circuit air brake, drum-type brake, with optional ABS 前后独立双回路气刹，鼓式刹车，可选配ABS					