

技术参数

牵引车 Tractor New J6P 4x2

Vehicle type 车辆类型		CA4180	CA4180	CA4180	CA4180
Drive mode 驱动方式		4X2	4X2	4X2	4X2
Cab 驾驶室		J6P high-top extended cab	New J6P high-top extended cab	J6P high-top extended cab	New J6P high-top extended cab
Engine 发动机	Model 型号	CA6DL2-35E3F	CA6DM2-42	CA6DL2-35E5	CA6DM2-46E52
	Displacement (L) 排量	8.6	11.04	8.6	11.05
	Maximum power (hp) 最大马力	350	420	350	460
	Rated speed (rpm) 额定转速	2,100	1,900	2,100	1,900
	Maximum torque/speed (Nm/rpm) 最大扭矩/转速	1500	1900	1500	2100
	Emission 排放标准	Euro II	Euro II	Euro V	Euro V
Transmission 变速箱	Model 型号	CA10TAX160M2	12JSD220TA-B	CA10TAX160M2	ZF16S2230
	Form/number of gears 档位	Manual/10 手动/10档	Synchronizer manual/12 同步器手动/12档	Manual/10 手动/10档	Synchronous manual/16 同步器手动/16档
	Forward gear ratio range 速比	10.9-0.74	12.1-0.78	10.9-0.74	13.8-0.84
Front axle load (kg) 前桥载荷 (kg)		7500	7500	7500	7500
Front suspension 前悬架		Parabolic springs 抛物线弹簧	Parabolic springs 抛物线弹簧	Parabolic springs 抛物线弹簧	Parabolic springs 抛物线弹簧
Rear axle load (kg) 后桥载荷 (kg)		13,000	13,000	13000	13000
Rear suspension 后悬挂		Parabolic springs 抛物线弹簧	Parabolic springs 抛物线弹簧	Parabolic springs 抛物线弹簧	4Airbags 气囊悬架
Rear axle model/speed ratio 后桥型号/速比		φ498/4.11	φ498/4.11	φ498/4.11	φ498/4.11
Chassis self weight (kg) 底盘自重 (kg)		6800	7000	6800	6700
Towing Weight (kg) 牵引质量 (kg)		35,000	35,000	35,000	35,000
Wheel base (mm) 轴距		3,600	3800	3600	3800
Saddle 鞍座		φ50	φ50	φ50	φ50
Tire 轮胎		12R22.5	12R22.5	12R22.5	315/80R22.5
Brake system 制动系统		Front and rear independent dual-circuit air brake, drum-type brake, with optional ABS 前后独立双回路气刹，鼓式刹车，可选配ABS			