

Technologies specifications

技术参数

Rigid Tractor JK6 4x2

Vehicle type 车辆类型		CA4186	CA4256
Drive mode 驱动形式		4X2	4X2
Cab 驾驶室		JK6 semi hight roof full-floating cab (4-point full-floating cab)	JK6 right-set flat top cab
Engine 发动机	Model 型号	解放 FAWDE CA6DL1-29E5	潍柴 WEICHAI WP10.380E32
	Displacement (L) 排量	7.7	9.7
	Maximum power (hp) 最大功率	290	380
	Rated speed (rpm) 额定转速	2,300	2,200
	Maximum torque/speed (Nm/rpm) 最大扭矩/转速	1150/1300-1700	1460/1200 ~ 1600
	Emission 排放标准	Euro V 欧五	Euro II 欧二
Transmission 变速箱	Model 型号	解放 FAW CA9TB160M	法士特 FAST 12JSD160T
	Form/number of gears 档位	Manual/9 手动/9	Manual/12 手动/12
	Forward gear ratio range 速比	14.34-1.0	15.53-1.0
Front axle load (kg) 前桥载荷		6500	6500
Front suspension 前桥悬挂		Multiple leaf spring 钢板弹簧	Multiple leaf spring 钢板弹簧
Rear axle load (kg) 后桥载荷		13,000	2×11500
Rear suspension 后桥悬挂		Multiple leaf spring 钢板弹簧	Multiple leaf spring 钢板弹簧
Rear axle model/speed ratio 后桥型号/速比		485/4.625	435/4.111
Chassis self weight (kg) 底盘自重		6,500	7,600
Allowable total weight of the vehicle (T) 载重		43,000	49,000
Wheel base (mm) 轴距		3,500	3300+1350
Cargo box size 货箱尺寸 (mm)		6750/ 7200	6,750
Tire 轮胎		275/80R22.5-18	275/70R22.5-16PR
Brake system 刹车系统		Front and rear independent dual-circuit air brake, drum-type brake, with optional ABS 前后独立双回路气刹，鼓式刹车，可选配ABS	