

Vehicle type 车辆类型		CA5250	CA5250
Drive mode 驱动形式		6×4	6×4
Cab 驾驶室		J6P flattop small semi-cab	J6P flattop small semi-cab
Engine 发动机	Model 型号	CA6DL2-35E3F	CA6DL2-35E5
	Displacement (L) 排量	8.6	8.6
	Maximum power (hp) 最大功率	350	350
	Rated speed (rpm) 额定功率	2,100	2,100
	Maximum torque/speed (Nm/rpm) 最大扭矩	1500	1500
	Emission 排放标准	EURO II 欧二	EURO V 欧五
Transmission 变速箱	Model 型号	CA10TA160M2	CA10TA160M2
	Form/number of gears 档位	Manual/10 手动/10	Manual/10 手动/10
	Forward gear ratio coverage 速比	14.7-1.0	14.7-1.0
Front axle load (kg) 前桥载荷		7500	7500
Front suspension 前桥悬挂		Multiple leaf spring 多片簧	Multiple leaf spring 多片簧
Rear axle load (kg) 后桥载荷		2×16000	2×16000
Rear suspension 后桥悬挂		4U heavy-duty 四骑马螺栓-重载	4U heavy-duty 四骑马螺栓-重载
Rear axle model/speed ratio 后桥型号/速比		φ300/5.26	φ300/5.26
Chassis weight (kg) 底盘自重		12000	12000
Total allowable weight of the vehicle (kg) 总质量		25000	25000
Wheel base (mm) 轴距		3800+1350	4050+1350
Truck bed dimension (mm)		10m³	10m³
Tire 轮胎		12.00R20	12.00R20
Brake system 制动系统		Front and rear independent dual-circuit air brake, drum-type brake, with optional ABS 前后独立双回路气刹，鼓式刹车，可选配ABS	